

Air Filter + Regulator + Lubricator

Mini Type 3 Units Air Combination


Series FRL700A

◆ How to Order

FRL700A – 02 N C H



Symbol



Drain type

Nil	Semi-auto drain
H	Manual drain

Filtration

Nil	5 μ m	C	40 μ m
-----	-------	---	--------

Thread

Nil	G	N	NPT
-----	---	---	-----

Port size

01	1/8	02	1/4
----	-----	----	-----

Air Filter+Regulator+Lubricator

FRL700A	Polycarbonate body
---------	--------------------

◆ Specifications

Model	FRL700A-01	FRL700A-02
Port size	1/8(option)	1/4(standard)
Fluid	Air	
Construction	Diaphragm type regulator	
Body material	Polycarbonate	
Bowl material	Polycarbonate(standard), Anti-acid & alkali(option)	
Filtration	5 μ m(standard),40 μ m(option)	
Set pressure range	0.05~0.8 MPa	
Max. Inlet pressure(standard)	0.8 MPa	
Max. flow rate	1850l/min	
Ambient and fluid temperature	-10℃~60℃(No freezing)	
Recommended lubricant	Turbin oil class 1(ISO VG32)	
Filter bowl capacity	35cc	
Lubricator bowl capacity	50cc	
Standard drain	Semi-automatic drain(below 0.05Mpa)	
Net weight	810g	
Accessories	1 Gauge, 1 bracket, 4 screw, 1 plug	

◆ Dimensions

